

RACK AND PINION JACKS WITH ADJUSTABLE BRACE 15-00-VK

Use and description:

Rack and pinion jacks **15-00-VK** are used for lifting or handling loads. They are portable tools used during installation, assembly, repair and other works.

Properties:

- robust, simple and „indestructible“ construction; lifting (expansion) using the head or adjustable side brace
- the adjustable side brace enables optimum use of the rack lift
- the option of setting 7 positions of the side brace
- will reliably hold the load in any position using the lock built into the hand crank
- acceptable actuating force in the crank
- increased comfort for operators in the version with ratchet crank (“RK” symbol)
- low maintenance demands



15-00-VK/2,5t

Characteristics:

Type	Loading capacity (t)		Acting force N	Weight kg
	Q1	Q2		
15-00-VK	2.5	1.8	380	15.0
15-00-VK	5	3.5	550	22.0
15-01-VK	10	7	540	38.0
15-01-VK	16	11.2	730	65.0
15-00-VK-RK*	2.5	1.8	380	16.0
15-00-VK-RK*	5	3.5	550	23.0
15-01-VK-RK*	10	7	540	39.0

* with ratchet crank

The product has been designed and constructed as the equipment group I (mine), category M2 and equipment group II (mine surface installations) category 2 according to the Directive 94/9/EC of the European Parliament and the Council and meets the requirements for using in areas “dangerous atmospheric conditions 2” according to EN 1127-2+A1 and “zone 1” according to EN 1127-1 on condition that all national regulations are fulfilled by the employer.