

DRILLING POSTS VP

Use and description:

Drilling posts type **VP** (hereinafter only posts) are used together with all existing pneumatic hand hammer drills and hand rotary drilling machines for drilling in coals manufactured in the Czech Republic. The are important auxiliary equipment making the work in mines and quarries easier so that they withstand all vibrations and weights of drilling machines during the drilling operation.

The drilling posts consist of a handle, telescopic part, valve body, gate valve and anchoring tip.



Characteristics:

Туре		VP 600	VP 800	VP 1000	VP 1200
Max. extension length	mm	600	800	1 000	1 200
Max. thrust force (*ca)	N	1 000	1 000	1 000	1 000
Air working pressure	MPa	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6	0.4 - 0.6
Air filtration	μ	30	30	30	30
Dimensions (I x w)	mm	1 280x270	1 480x270	1 680x270	1 880x270
Air feeding hose	mm	Js 13, 16, 20			
Weight (*ca)	kg	16.9	19.0	20.7	22.4

^{*} for compressed air overpressure 0.50 MPa tolerance ± 10%

The product has been designed and constructed as the equipment group I (mine), category M2 according to the Directive 94/9/EC of the European Parliament and the Council and meets the requirements for using in areas "dangerous atmospheric conditions 2" according to EN 1127-2+A1 on condition that all national regulations are fulfilled by the employer.

U Cementárny 1303/16 703 00 Ostrava – Vítkovice, Czech Republic http://www.koexpro.cz; www.koexpro.eu phone: +420 595 782 251, +420 595 782 250 fax: +420 596 633 923, +420 595 782 249

e-mail: koexpro@koexpro.cz