

SUSPENDED CARRIER FOR PALETTES ZNP 1500

Use and description:

Suspended carrier for pallets **ZNP 1500** is intended for placing and transport of ISO pallets 800 x 1200 mm with loading capacity 1500 kg. The carrier has been designed and constructed so that it is possible to transport it using all suspended monorail transport systems. Its dimensions enable to transport it on the mine timber cars having the width bigger than 950 mm.

The suspended carrier consists of the pallets carrier and cross beam. Four high strength chains are parts of the cross beam. In case of smaller rout profile height it is possible to shorten the chains as necessary and so to enable the set going through such profile due to smaller carrier cross section. The suspended carrier has been designed and constructed for the monorail carrying trolley type TDS 4/A of the ZAMPRA company.

The hanging system enables the transport both on horizontal and inclined rout sections of the mine openings. It is possible to transport the pallet to the place of destination with original fixation foil.



Characteristics:

Type		ZNP 1500
Loading capacity	kg	1 500.0
Weight	kg	99.5
Effective volume of standard container	m ³	0,768
Dimensions (l x w x h)	mm	1 265x915x1 300
Hanging up pin diameter	mm	40

Type marking: **ZNP**
ZNP PALETT SUSPENDED CONTAINER

The product has been designed and constructed as the equipment group I (mine), category M2 according to the Directive 94/9/EC-ATEX of the European Parliament and of the Council and meets the requirements for using in areas "hazardous atmospheric conditions 2" according to EN 1127-2+A1 on condition that all employer's national regulations are fulfilled.

U Cementárny 1303/16
703 00 Ostrava – Vítkovice, Czech Republic
[http:// www.koexpro.cz](http://www.koexpro.cz); www.koexpro.eu

phone: +420 595 782 251, +420 595 782 250
fax: +420 596 633 923, +420 595 782 249
e-mail: koexpro@koexpro.cz